



Typical Applications

Petroleum Refineries

Ethanol Facilities

Chemical Plants

Waste Water and Water
Treatment Plants

Power Generating Plants

Industrial Perimeters

Paper Mills

Foundries

Manufacturing Plants



Predator® LED Floodlighting

Hazardous Location

The Holophane® hazardous Predator LED floodlights are built to withstand the harshest environments without sacrificing performance. Versatile and efficient, hazardous Predator LED floodlights offer superior field-to-beam ratios in a rugged, corrosion-resistant housing. Available in two models; the hazardous Predator LED floodlight offers one-for-one replacements for 100W to 1000W HID while offering up to 77% energy savings.

- + Available in large and medium for direct replacement of 100W - 1000W HID
- + Listed UL/CUL1598 for wet location at 104°F (40°C) and rated IP66 for high-pressure hose-down applications
- + Predator HPFM available in 5,000 - 15,000 lumens for replacement of 100W - 400W HID
- + Predator HPFL available in 16,000 - 32,000 lumens for replacement of 400W - 1000W HID
- + Uniform illumination for any application, 4X4, 4X5, 5X5, 6X5, 6X6 NEMA patterns
- + Borosilicate prismatic glass lens that won't fade or discolor, optimizing light levels over time
- + 4000K or 500K CCT



Contact your local Holophane sales rep for more information or visit www.Holophane.com.

Predator® LED Floodlight

Hazardous Location

BOROSILICATE PRISMATIC GLASS LENS that won't fade, discolor or degrade in harsh environments

STANDARD WRAPAROUND YOKE MOUNT

JUNCTION BOX WIRING OPTION
for easier installation

ROBUST THERMAL MANAGEMENT SYSTEM for long life

Contact your local Holophane sales rep for more information or visit www.Holophane.com.

UL844 Listings:

- Class I, Division II
- Groups A,B,C,D